

U20000W UNIGIZER™

All the power you expect from a Speedrite energizer, with built in Bluetooth® connectivity and built-in Wi-Fi capability allowing internet access for remote monitoring and control.



STRONGER & SMARTER: MEET OUR NEXT-GEN UNIGIZER.

The Speedrite U20000W Unigizer™ is ideal for farmers that want a powerful three in one energizer with a robust design and intuitive interface.

MONITOR & CONTROL FROM YOUR PHONE

With built-in Bluetooth® and Wi-Fi compatibility, the Datamars Pro App provides the ability to monitor and control the energizer from a phone, locally and remotely.

ROBUST & INTUITIVE DESIGN

Improved output terminal design provides easier and more robust connection to the fence, with an updated industrial design to match the flagship W-series energizers (31000W, 46000W, 86000W).

CONTINUOUS POWER


Solar, battery and mains power with new battery back-up, providing continuous power to the fence even during blackouts to the mains supply.

- ✓ **CONTROL AND MONITOR VIA BLUETOOTH® AND RECEIVE ALERTS WHEN CONNECTED ON WI-FI***
- ✓ **LED INDICATORS DISPLAY OUTPUT VOLTAGE FOR QUICK DIAGNOSTICS**
- ✓ **MAINS, BATTERY (SOLD SEPARATELY) OR SOLAR CAPABLE**
- ✓ **CONNECT TO MAINS AND EXTERNAL BATTERY (SOLD SEPARATELY) SIMULTANEOUSLY FOR POWER DURING OUTAGE**
- ✓ **FENCE REMOTE TURNS ENERGIZER ON/OFF FROM THE FENCE (SOLD SEPARATELY)**
- ✓ **CYCLIC WAVE™ DELIVERS CONTINUOUS POWER ALONG THE ENTIRE FENCE**
- ✓ **SPLIT BOLT TERMINALS CONNECT MULTIPLE FENCE WIRES**
- ✓ **DATAMARS PRO APP MONITORS AND CONTROLS ENERGIZER FROM YOUR PHONE**
- ✓ **3 YEAR WARRANTY**

*Requires internet connection

SPECIFICATIONS

Product number	880 0013-470 ENGR SPE U20000W CA CO EC MX VE US-PLUG
	880 0013-471 ENGR SPE U20000W AR
	880 0013-472 ENGR SPE U20000W BO BR CL KR PE PY UY CEE 7/16 (EURO)PLUG
	880 0013-473 ENGR SPE U20000W HK MY PH SG UK-PLUG
	880 0013-474 ENGR SPE U20000W AU NZ
	880 0013-475 ENGR SPE U20000W JP
Output energy Stored energy	20 J 27 J
Battery input & typical current consumption	12 V 1.5 A (at full power and Wi-Fi connected)
Operating temperature	-15 to 50 °C (5 to 122 °F)
Minimum number of earth rods	6
Product size (W x H x D) Carton size (W x H x D) Product weight Carton weight	215 mm x 310 mm x 125 mm 393 mm x 216 mm x 136 mm 4.5 KG 4.85 KG
Typical output voltage performance Open circuit Standard load (500 Ω) Heavy load (100 Ω)	Up to 10000 V Up to 8900 V Up to 6300 V



Fence conditions can have a major impact on the effectiveness of any electric fence. Fence condition is dependent upon a number of factors including fence layout, vegetation, grounding conditions, age and state of repair.

Although the information presented in this Product Datasheet is believed to be accurate and reliable, no responsibility for inaccuracies can be assumed by Datamars. Performance data is typical only and variations due to component manufacturing tolerances are normal. Datamars reserves the right at any time to change performance characteristics or specifications without prior notice.

© Datamars – All rights reserved. 4357SPE02 ISSUE 2 03/26